Serial No.: 10/741,676

Filed : December 19, 2003

: 2 of 11 Page

AMENDMENTS TO THE CLAIMS:

This listing of claims replaces all prior versions and listings of claims in the

application:

LISTING OF CLAIMS:

1. (Currently Amended) A processor, comprising:

an authentication buffer configured to store authentication data including

ciphered-network-packet data subject to authentication, network packet data subject only

to authentication and not to ciphering, and network packet data subject to ciphering and

authentication, wherein the authentication buffer includes a circular first-in-first-out

(FIFO) arrangement; and

at least one authentication core coupled to the authentication buffer to

authenticate the authentication data from the authentication buffer.

2. (Previously Presented) The processor of Claim 1, wherein the circular FIFO

arrangement includes a moveable start of data pointer and a moveable end of data

pointer.

Applicants: Sydir et al. Attorney's Docket No.: INTEL-019PUS
Serial No.: 10/741,676 Intel Docket No. P18172

Filed: December 19, 2003

Page : 3 of 11

3. (Currently Amended) The processor of Claim 1, wherein the network processor further includes at least one cipher core adapted to operate with a cipher algorithm and the at least one authentication core is adapted to operate with an authentication algorithm, and a size of the authentication buffer is selected in accordance with a data block size associated with the cipher algorithm and a data block size associated with the authentication algorithm.

- 4. (Previously Presented) The processor of Claim 1, wherein the authentication core is adapted to authenticate the authentication data from the authentication buffer as blocks of authentication data.
 - 5. (Currently Amended) A network, comprising: a network processor comprising having:

an authentication buffer configured to store authentication data including at least one of comprising ciphered-network-packet data subject to authentication, network packet data subject only to authentication and not to ciphering, and network packet data subject to ciphering and authentication, wherein the authentication buffer includes a circular first-in-first-out (FIFO) arrangement; and

at least one authentication core coupled to the authentication buffer to authenticate the authentication data from the authentication buffer.

Serial No.: 10/741,676

Filed : December 19, 2003

Page : 4 of 11

6. (Previously Presented) The network of Claim 5, wherein the circular FIFO arrangement includes a moveable start of data pointer and a moveable end of data pointer.

7. (Original) The network of Claim 5, wherein the network processor further includes at least one cipher core adapted to operate with a cipher algorithm and the at least one authentication core is adapted to operate with an authentication algorithm, and a size of the authentication buffer is selected in accordance with a data block size associated with the cipher algorithm and a data block size associated with the authentication algorithm.

- 8. (Original) The network of Claim 5, wherein the authentication core is adapted to authenticate the authentication data from the authentication buffer as blocks of authentication data.
- 9. (Currently Amended) A method of authenticating network packet data, comprising:

moving to an authentication buffer authentication data, the authentication buffer configured to store the authentication data including at least one of comprising cipherednetwork-packet data subject to authentication, network packet data subject only to authentication and not to ciphering, and network packet data subject to ciphering and

Serial No.: 10/741,676

Filed : December 19, 2003

: 5 of 11 Page

authentication, wherein the authentication buffer includes a circular first-in-first-out

(FIFO) arrangement; and

moving to an authentication core a block of data from the authentication buffer.

10. (Original) The method of Claim 9, wherein the moving to an authentication

buffer authentication data comprises selecting the authentication buffer from among a

plurality of authentication buffers.

11. (Original) The method of Claim 9, further including:

setting a start of data pointer and an end of data pointer to respective initial

locations;

setting the end of data pointer in accordance with the moving the authentication

data to the authentication buffer; and

setting the start of data pointer in accordance with the moving to the

authentication core the block of data from the authentication buffer.

12. (Previously Presented) The method of Claim 9, wherein the circular first-in-

first-out (FIFO) arrangement includes a moveable start of data pointer and a moveable

end of data pointer.

13. (Original) The method of Claim 9, further including:

Serial No.: 10/741,676

: December 19, 2003

Page : 6 of 11

providing a cipher core adapted to operate with a cipher algorithm;

providing the authentication core adapted to operate with an authentication

algorithm, and

sizing the authentication buffer in accordance with a data block size associated

with the cipher algorithm and a data block size associated with the authentication

algorithm.

14. (Currently Amended) A computer storage readable medium that stores

instructions thereon to authenticate network packet data, the instructions causing a

machine to:

move to an authentication buffer authentication data, the authentication buffer

configured to store the authentication data comprising including at least one of ciphered-

network-packet data subject to authentication, network packet data subject only to

authentication and not to ciphering, and network packet data subject to ciphering and

authentication, wherein the authentication buffer includes a circular first-in-first-out

(FIFO) arrangement; and

move to an authentication core a block of data from the authentication buffer.

15. (Previously Presented) The medium of Claim 14, wherein the instructions

causing a machine to move to an authentication buffer authentication data comprises

Serial No.: 10/741,676

: December 19, 2003

Page : 7 of 11

instructions causing a machine to select the authentication buffer from among a plurality

of authentication buffers.

16. (Previously Presented) The medium of Claim 14, further comprising

instructions causing a machine to:

set a start of data pointer and an end of data pointer to respective initial locations;

set the end of data pointer in accordance with the moving the authentication data

to the authentication buffer; and

set the start of data pointer in accordance with the instructions for moving to the

authentication core the block of data from the authentication buffer.

Claim 17 (Cancelled)

18. (Previously Presented) The medium of Claim 14, further comprising

instructions causing a machine to:

provide a cipher core adapted to operate with a cipher algorithm;

provide the authentication core adapted to operate with an authentication

algorithm, and

size the authentication buffer in accordance with a data block size associated with

the cipher algorithm and a data block size associated with the authentication algorithm.